

## ASSEMBLY AND INSTALLATION

### INSTRUCTIONS

**WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF MAIN POWER SUPPLY WHILE INSTALLING OR SERVICING THIS FIXTURE. WE STRONGLY RECOMMEND THAT A QUALIFIED ELECTRICIAN INSTALL THIS FIXTURE.**

#### Install Steps:

1. Fasten the cross bar to the outlet box (ceiling) with the outlet box screws.
2. Attach the end fonts to the bar by inserting clip of the end fonts inside the bar, then attach the cap (**packed with the canopy**) by screwing the down loop.
3. Choose a certain length of chain you need, then spread both end of the chain to clamp securely the top loop and the down loop.
4. Thread the fixture wires and earth wires through the chain link, top loop and the canopy.
5. Make wire connections with wire nuts.
  - Smooth wire of fixture to live wire of supply.
  - Ribbed wire of fixture to neutral wire of supply.
  - Ground wire (bare copper wire) to ground wire of supply or attach the ground wire of fixture to the cross bar with green screw, then connect the end of ground wire to ground wire of supply with wire nut.
6. Attach the canopy to the nipple of the cross bar with the knob.
7. Attach the lamp shade to the socket with the socket ring.
8. Install lamp bulb to socket (please do not exceed the maximum wattage which is recommended on label).

