

# Speedtiles

ULTRA  
ADHESIVE

## Range Backsplash

### INSTALLATION INSTRUCTIONS

IMPORTANT: Prior to installation you must assemble the backsplash on a tabletop or large flat surface.

#### RANGES

Tools: Spray Bottle | Measuring Tape | Pencil | Silicone

##### STEP 1

Pull the range completely out of the way and thoroughly wash the surface of the wall space below the range hood and allow to dry.

##### STEP 2

Fill the spray bottle to 3/4 full with warm water & add 2 teaspoons (5-10ml) of dishwashing soap.

##### STEP 3

Measure the width of your range hood and mark a vertical line at the center point on the wall with a pencil

##### STEP 4

Select the backsplash strip labeled TOP and mark a vertical line at the center point on the face of the strip with the pencil. Turn the strip over and completely peel off the backing paper. Spray the adhesive surface with the prepared soap & water solution. Make sure the entire surface is moist.

##### STEP 5

Align the center mark on the TOP strip with the center mark on the wall with the interlocking edge pointed down. Once aligned adjust the strip to ensure that the top is flush with the bottom edge of the vent hood. Push the strip flat and firmly wipe dry with a clean cloth.

##### STEP 6

Select a strip and test the fit against the installed TOP strip. To install completely peel off the backing. Spray the adhesive surface with the prepared soap & water solution. Make sure the entire surface is moist. Align the strip, push the strip flat, hold it for a couple of seconds and wipe dry with a clean cloth.

##### STEP 7

Repeat the previous steps until all the strips have been installed and finish using the strip marked BOTTOM.  
*NB: When installing LINOX strips be sure each one is pointing up as indicated on the triangles.*

##### STEP 8

Wait 2-3 hours to allow the water to evaporate. Remove the protective film from the face of all the installed strips

##### STEP 9

Select one piece of finishing trim and dry test the fit (with the wide edge facing out) along the left side of the installed strips. To install remove the backing tape and press the trim firmly into position. Repeat the process on the right side. To finish, apply a bead of silicone along the edge where the backsplash meets the countertop. To ensure maximum durability apply a thin bead of silicone where the edge of the trim meets the wall.

#### COOKTOP

Tools Needed: Spray Bottle | Measuring Tape | Pencil Ruler | Utility Knife | Hacksaw | Caulking Gun & Caulking  
*Always wear eye protection when cutting SpeedTiles® products*

##### STEPS 1 - 6

Follow Steps 1 through 6 as indicated above in the instructions for installing a backsplash for RANGES.

##### STEP 7

Repeat the previous steps until only 2 strips remain, including the strip marked BOTTOM.

##### STEP 8

Measure the space remaining between the last strip installed and the countertop to determine if there is enough space for both remaining strips. If there is not enough space, cut the unmarked strip to size. Test the fit of the cut strip prior to removing the backing. When the fit is correct install the strip. Follow STEP 9 when there is space for both strips.

##### STEP 9

Select the strip marked BOTTOM. Measuring from the interlocking edge make a mark on the face of the strip on both the left and right sides. Draw a straight line to join the marks across the face of the strip with the ruler. Use the ruler as a straight edge and with a utility knife cut the strip. Test the fit of the cut strip prior to removing the backing. When the fit is correct install the strip.

##### STEP 10

Wait 2-3 hours to allow the water to evaporate. Remove the protective film from the face of all the installed strips.

##### STEP 11

Select the 2 pieces of finishing trim and cut both to the desired length using the hacksaw. Test the fit (with the wide edge facing out) along the left side of the installed strips. To install remove the backing tape and press the trim firmly into position. Repeat the process on the right side to complete the installation.

##### STEP 12

To finish, apply a bead of caulking along the edge where the backsplash meets the countertop. To ensure maximum durability apply a thin bead of silicon where the edge of the trim meets the wall.

Visit [speedtiles.com](http://speedtiles.com) to watch the installation video

